


Product : Shrink tape
Job : Shrink wrap
Users : Professional

Width : 3,7 in / 9,6 cm
Length : 180 ft / 55 ml



Backing: UV Stabilized LDPE Film
Adhesive: Rubber
Liner: N/A
Colors: White



Construction

Un coté	Collant
Adhésif	Caoutchouc
Dos	Polyéthylène
Couleur	Blanc

Applications

- Long term preservation, sealing, and splicing applications.
- Direct protective mask on aircraft, trucks, boats, and industrial equipment during outdoor storage.
- Can be used in conjunction with outdoor shrink film to secure and seal the shrink film border firmly during transportation or extended outdoor storage.

Bénéfits - Film LDPE

- Conformable for irregular surfaces
- Abrasion resistant
- UV and weather resistant
- Moisture, solvent, and chemical resistant

Bénéfits - Rubber adhesive

- Good quick stick
- Excellent adhesion to PE and Shrink film
- Clean removal from most surface
- Resists staining and gosting
- Excellent low-temperature adhesion

Features

- Heavy duty PE backing.
- UV and weather resistant.
- Highly conformable.
- Non-staining.
- Clean removal, rubber based adhesive.
- Excellent shrink properties.

Données technique

Total thickness	9,0 mils / 0,229 mm
Adhesion to steel	65 oz/in / 45 N/cm
Tensile strength	25 lb/in / 43 daN/cm
Elongation	120%
Application température	41°F to 122°F / 5°C to 50°C
Operating température	176°F / 80°C for 30 minutes
Recommended storage condi	40 - 60 % humidity & 60°F-80°F
Standard shelf life	12 Months from shipment date

IMPORTANT: Read the user manual before use - For use only in sufficiently well ventilated rooms.

GUILBERT EXPRESS reserves the right to change product characteristics without prior notice. Actual products may differ from photographs

www.shrink-wrapping.express - info@shrink-wrapping.express