IORNET AND POWERFUL

GUARANTEE 2 years Parts and

GET TO WORK

- Single-click hose connection, thanks to the fast connector.
- **o** Readily available flame thanks to synchronised piezo ignition, with a single press on the trigger.
- o Interchangeable burners, with no tools needed.
- o Easy self-maintenance: changing the trigger / piezo-ignition also requires no tools.

POWER AND PRECISION

LIGHTWEIGHT

Offering a high level of performance with its targeted flame, the HORNET gun has a range of burners from 30 to 160 kW.

USER COMFORT

- o Very lightweight (about 500 g), to reduce the risk of musculoskeletal disorders (MSDs).
- Attenuated sound level (< 81 dBA).
- o Ready-to-use gun, operational in less than a minute, comes in a carrying case.
- Control power through the level of pressure exerted on the trigger.
- Spare trigger / piezo-ignition included in the pack.

ENVIRONMENTAL APPROACH

The safety-handle that equips HORNET gun contributes the to a significant reduction in gas consumption and therefore:

o reduces CO2 emissions,

o avoids the risk of causing accidental fires on worksites and related harm to people and property.



AFTER-SALES SERVICE

o Guaranteed for 2 years. o Response in less than 24 hours.

SAFETY

EXPRESS

• Safe ignition with low gas flow.

- **o** Three-position marking: changing burner, storage, ignition.
- o Safety handle (the gun switches off when the operator releases the handle).
- **o** Fitted with safety valve in case of hose breakage.
- **o** Professional guality rubber hose to ISO 3821 standard.
- **o** Gun supplied with gloves specially designed to provide optimum heat resistance.





LOGISTIC/CRATING	C EXPRESS	BUR	NERS			9 2	ye Parts labo	ATEE ars our			
						1031	1071	1091	1151	1161	1912
in annous		1031	(1071) (1091)	Ø BURNER (mm)	35	41	50	50	50	30
		30 kW	70 kW	90 kW	(in)	1.3	1.6	1.9	1.9	1.9	1.1
23						158	170	210	325	383	260
		1151 1	60 kW ⊂		WEIGHT (g) (lb)	0.3	0.3	0.4	0.7	0.8	0.5
AND E MAN					CONSUMPTION (kg/h)	2.58	5.22	6.77	11.8	11.8	6.77
		1161 1	60 kW <⊲		(lb/h)	5.6	11.5	14.9	26	26	14.9
					POWER (kW /4 bar)	30	70	90	160	160	90
		1912 9	0 kW 1 25	gth : m - 49.2 in	(BTU at 58 psi)	102 400	245 800	319 000	553 000	553 000	319 000
A MANY			1,20		FLAME L (mm)	250	350	350	1 100	1 100	300
WINTER STORAGE					(in)	9.8	13.7	13.7	43.3	43.3	11.8
WINTER STORAGE					Ø FLAME (mm)	45	55	65	65	65	140-160
		CKS 🍾			(in)	1.7	2.1	2.5	2.5	2.5	5.5-6.2
All - and - and					SOUND LEVEL (dBA)	77	79	81	81	81	85
CONTAINMENT / SCAFFOLDING	10701 70 kW 80-320 μm PE - BD) (10731 30 kW + 70 kW) (<u>1090</u> 90 kV	1) (10931) V 30 kW + 90 kW	Dis	stributor	stamp				1912 30 1.1 260 0.5 6.77 14.9 90 319 000 300 11.8 140-160 5.5-6.2 85

Guilbert Express Contact: Philippe Réveillion Tel.: +33 (0)6 70 79 35 61 www.shrink-wrapping.express