

WIZZ

HIGH POWERFLAME TEMPERATURE & SURFACE AREA



GET TO WORK

- Single-click hose connection, thanks to the **fast connector**.
- Readily available flame thanks to **synchronised piezo ignition**, with a single press on the trigger.
- **Interchangeable burners**, with no tools needed.
- Easy **self-maintenance**: changing the trigger / piezo-ignition also requires no tools.

POWER

Offering a high level of performance with its large flame, the WIZZ gun has a range of burners from 50 to 150 kW (171 000 to 511 500 BTU/h).

USER COMFORT

- **Very lightweight** (about 650 g), to reduce the risk of musculoskeletal disorders (MSDs).
- Ready-to-use gun, operational in less than a minute, comes in a carrying case.
- Control power through the level of pressure exerted on the trigger.
- Spare trigger / piezo-ignition included in the pack.



AFTER-SALES SERVICE

- Guaranteed for 2 years.
- Response in less than 24 hours.

ENVIRONMENTAL APPROACH

The safety-handle that equips the WIZZ gun contributes to a significant reduction in gas consumption and therefore:

- reduces CO2 emissions,
- **avoids the risk of causing accidental fires** on worksites and related harm to people and property.

SAFETY

- **Safe ignition with low gas flow**.
- Three-position marking: changing burner, storage, ignition.
- **Safety handle** (the gun switches off when the operator releases the handle).
- Fitted with **safety valve** in case of hose breakage.
- Professional quality rubber hose to ISO 3821 standard.
- Gun specially designed to provide optimum heat resistance.



Shrink wrapping



LOGISTIC/CRATING



PIPELINE



CONTAINMENT / SCAFFOLDING



GUARANTEE
2 years
Parts and labour



5 PACKS



10165

341 000 BTU/h
L 5.12 in




10163

511 500 BTU/h
L 5.12 in




10166

341 000 BTU/h
L 15.75 in




10164

511 500 BTU/h
L 15.75 in





10167

341 000 BTU/h
L 23.62 in



6 BURNERS Cat. No.	150WL400	150WL200	100WL600	100WL400	100WL200	50WL200
Ø BURNER (mm) (in)	70 2.75	70 2.75	60 2.36	60 2.36	60 2.36	50 1.97
WEIGHT (g)	310	225	325	300	220	205
CONS. (g/h) (lb/h)	10860 23.95	10860 23.95	7390 16.30	7390 16.30	7390 16.30	3910 8.60
POWER (kW /4 bar) (BTU/h - 58 psi)	150 511 500	150 511 500	100 341 000	100 341 000	100 341 000	50 171 000
L FLAME (mm) (in)	1000 39.37	1000 39.37	800 31.50	800 31.50	800 31.50	650 25.59
Ø FLAME (mm) (in)	130 5.12	130 5.12	120 4.72	120 4.72	120 4.72	110 4.33



Distributor stamp

Maxxair - Crédit photo - EMBALAJES CANTABRIA, Solicom. Photos not binding. Guilbert Express reserves the right to change the features of the products described, without notice. All rights reserved. The photos must not be reproduced, modified or transmitted, in whole or in part, in any form or using any method whatsoever, without the prior written permission of Guilbert Express, May 2018.