GUILBERT EXPRESS Le Péripole - Lot 209-21033 33 avenue du Maréchl de Lattre de Tassigny F- 94127 Fontenay sous Bois Cedex Tel.: +33 (0) 825 800 251 - Fax: +33 (0) 825 800 238



Shrink wrapping

Shrink tape Cat. No. 42644

Product : Job : Users :

of glue

Gaffer Shrink wrap Professional

by hand in both directions

Nichiban 1200 Canvas Adhesive is very durable and yet easy to unwind and tear

Excellent adhesion (even on rough or fibrous surfaces), all without leaving traces

A very high quality adhesive tape with a thickness of 0.31 mm

Each roll is individually wrapped in cellophane for long-term storage

Very stable, resistant to wear, friction and moisture

The best price / performance ratio of the market

Width : Length :



Applications

- Long term preservation, sealing, and splicing applications.
- Direct protective mask on aircraft, trucks, boats, and industrial equipment during outdoor storage.
- Can be used in conjunction with outdoor shrink film to secure and seal the shrink film border firmly during transportation or extended outdoor storage.

Bénefits - Film PE

- Abrasion resistant
- UV and weather resistant
- Moisture, solvent, and chemical resistant

Bénefits - Rubber adhesive

- Good quick stick
- Excellent adhesion to PE and Shrink film
- Clean removal from most surface
- Resists staining and gosting
- Excellent low-temperature adhesion

Features

- Heavy duty PE backing.
- UV and weather resistant.
- Non-staining.
- Clean removal, rubber based adhesive.

Données technique

.Width	50 mm
.Length	50 m
.PE	coated coating, smooth
.Finish	Gloss
.Thickness	0.31mm
.Support	Rayon Canvas
.mesh	80
.Adhesive	Rubber

IMPORTANT: Read the user manual before use - For use only in sufficiently well ventilated rooms

GUILBERT EXPRESS reserves the right to change product characteristics without prior notice. Actual products may differ from photographs www.shrink-wrapping.express - info@shrink-wrapping.express